

County Surveyor's Record, Douglas County, Oregon

North Bdy. of T. 21 S., R. 11 W.

CHAINS

75.50	A branch, 1 lk. wide, course S.	-50
80.00	A fir, 4 ins. dia., which I marked T 20 S S 33 on NE., R 11 W S 4 on SE., T 21 S S 5 on SW., S 32 on NW. sides, with 2 notches on W. and 4 notches on E. sides, for cor. to secs. 4, 5, 32 & 33; from which A fir, 33 in. dia., bears N.75°E., 43 lks. dist., marked T 20 S R 11 W S 33 B T. A fir, 5 ins. dia., bears S.8½°E., 8 lks. dist., marked T 21 S R 11 W S 4 B T. An alder, 5 ins. dia., bears S.66°W., 11 lks. dist., marked T 21 S R 11 W S 5 B T. A fir, 4 ins. dia., bears N.1°W., 18 lks. dist., marked T 20 S R 11 W S 32 B T.	
	West, on true line, bet. secs. 5 & 32. Var. 20°6'E. Along S. slope of a flat covered by small hemlocks.	
12.50	A gulch, course S.	-50
17.50	Top of dividing ridge, bears N. & S.; begin descent of a steep NW. slope.	+120
23.00	A canyon, course NW.	-200
27.75	Top of spur, bears NW. & SE.; descend through a timber flat.	+50
36.00	Descend along S. slope.	
40.00	A cedar, 36 ins. dia., which I marked ¼ S. on N. side, for ¼ sec. cor.; from which An alder, 14 ins. dia., bears S.53°E., 34 lks. dist., marked ¼ S B T. A spruce, 10 ins. dia., bears N.36°E., 12 lks. dist., marked ¼ S B T. Descend steep S. slope.	
42.00	A canyon, course NW.	-80
45.50	Top of spur, bears N. & S.	+75
51.20	A creek, 6 lks. wide, course S.	-80
53.00	A branch, 2 lks. wide, course SE.	
54.00	Begin to ascend.	