

North Bdy. of T. 21 S., R. 11 W.

CHAINS		
58.75	Top of spur, bears NE. & SW.	+200
62.00	A canyon, course NE.; begin very steep ascent.	
65.25	Top of spur, bears N. & S.	+300
68.75	Top of spur, bears N. & S.	+100
71.00	Top of ridge, bears N. & S.; begin to descend S. slope.	+60
80.00	Set a post, 4½ ft. long, 4 ins. sq., 24 ins. in the ground, for cor. to secs. 5, 6, 31 and 32, marked T 20 S S 32 on NE., R 11 W S 5 on SE., T 21 S S 6 on SW., S 31 on NW. faces, with 1 notch on W. and 5 notches on E. edges; from which A fir, 27 ins. dia., bears N.56½°E., 26 lks. dist., marked T 20 S R 11 W S 32 B T. A fir, 36 ins. dia., bears S.29½°E., 35 lks. dist., marked T 21 S R 11 W S 5 B T. A fir, 42 ins. dia., bears S.22°W., 20 lks. dist., marked T 21 S R 11 W S 6 B T. An alder, 6 ins. dia., bears N.12½°W., 8 lks. dist., marked T 20 S R 11 W S 31 B T. Aug. 17th, 1891.	
West, on true line, bet. secs. 6 and 31. Var.20°13'E.		
Descend N. slope.		
7.00	A canyon, course SE.	-400
9.80	Top of spur, bears SE. & NW.	+200
13.75	A branch, 5 lks. wide, course S.	-150
19.00	Top of spur, bears N. & S.	
24.25	Top of spur, bears N. & S.	
30.25	Top of spur, bears N. & S.	
35.00	A branch, course S., 2 lks. wide.	-200
40.00	Set a post, 3 ft. long, 3 ins. sq., 18 ins. in the ground, for ¼ sec. cor., marked ¼ S on N. face; from which A fir, 36 ins. dia., bears N.8°W., 16 lks. dist., marked ¼ S B T. A fir, 48 ins. dia., bears S.29°W., 45 lks. dist., marked ¼ S B T.	