

County Surveyor's Record, Douglas County, Oregon

North Bdy. of T. 21 S., R. 11 W.

CHAINS

44.00 Top of spur, bears NE. & SW. +100

46.00 A canyon, course SW.; begin ascent. -120

53.25 Top of dividing ridge, bears NE. & SW.; begin descent of +600
S. slope.

65.50 A dry branch, course SE.; begin ascent. -300

77.20 Intersect West bdy. of Tps., 295 lks. S. of cor. to Tps.
20 & 21 S., Rs. 11 & 12 W., which is a decayed post, 4
ins. sq., marked T 20 S S 31 on NE., R 11 W S 6 on SE.,
T 21 S S 1 on SW., R 12 W S 36 on NW. faces, with 6
notches on each edge; from which

A fir, 15 ins. dia., bears N.5½°E., 43 lks. dist.,
marked T 20 S R 11 W S 31 B T.

A fir, 15 ins. dia., bears S.63°E., 17 lks. dist.,
marked T 21 S R 11 W S 6 B T.

A fir, 15 ins. dia., bears S.85°W., 62 lks. dist.,
marked T 21 S R 12 W S 1 B T.

A fir, 12 ins. dia., bears N.8½°W., 48 lks. dist.,
marked T 20 S R 12 W S 36 B T.

At point of intersection I set a post, 4½ ft. long, 4
ins. sq., 24 ins. in the ground, for closing cor. to
Tps. 20 & 21 S., R. 11 W., marked T 20 S S 31 on N.,
C C R 11 W on E., T 21 S S 6 on S. faces, with 6 notches
on N., S. & E. faces; from which

A fir, 40 ins. dia., bears N.6°E., 32 lks. dist.,
marked T 20 S R 11 W S 31 B T.

A spruce, 5 ins. dia., bears S.62°E., 40 lks. dist.,
marked T 21 S R 11 W S 6 B T.

A fir, 40 ins. dia., bears N.43°W., 31 lks. dist.,
marked C C T 20 & 21 S R 11 W B T.

August 18th, 1891.