

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 11 W.  
 Survey by Wm. Thiel under Contract 567 dated Feb. 16th, 1891.

CHAINS

From the cor. to secs. 25, 26, 35 & 36, which is a post,  
 4 ins. sq., marked T. 20 S S 25 on NE., R 11 W S 36 on  
 SE., S 35 on SW., S 26 on NW. faces, with 1 notch on S.  
 & E. edges; from which

An alder, 10 ins. dia., bears N.53°E., 75 lks. dist.,  
 marked T 20 S R 11 W S 25 B T.

An alder, 12 ins. dia., bears S.77½°E., 60 lks. dist.,  
 marked T 20 S R 11 W S 36 B T.

A hemlock, 6 ins. dia., bears S.21°W., 10 lks. dist.,  
 marked T 20 S R 11 W S 35 B T.

An alder, 8 ins. dia., bears N.72°W., 28 lks. dist.,  
 marked T. 20 S R 11 W S 26 B T.

East, on a random line, bet. secs. 25 & 36.

Va.20°10'E.

40.00 Set temp. ¼ sec. cor.

80.20 Intersect East boundary of Tp., 13 lks. S. of cor. to  
 secs. 25, 36, 30 & 31.

May 10th, 1892.

Thence I run

S.89°54'W., on true line, bet. secs. 25 & 36.

Va.20°19'E.

Ascend.

7.00 Top of ridge, bears SE. & NW.; descend. +290

18.50 A canyon, course S.; ascend. -150

20.50 Top of spur, bears S. & N.; descend. +60

24.00 A canyon, course SE.; ascend. -75

30.40 Top of spur, bears S. & N.; descend. +185

36.50 A canyon, course S. -160

38.25 A canyon, course SE.

40.10 Set a post, 3 ft. long, 3 ins. sq., 18 ins. in the ground,  
 for ¼ sec. cor., marked ¼ S on N. face; from which

A cedar, 36 ins. dia., bears S.87°W., 24 lks. dist.,  
 marked ¼ S B T.

A fir, 24 ins. dia., bears N.88°E., 16 lks. dist.,  
 marked ¼ S B T.

Ascend.