

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 11 W.

CHAINS		
46.50	Top of spur, bears E. & W.; ascend S. slope.	+150
53.00	Top of ridge, bears E. & W.; descend.	+20
58.25	A gulch, course NW.	-100
70.25	A gulch, course N.65°E.; descend NW. slope.	-100
80.20	The cor. to secs. 25, 26, 35 and 36.	
May 11th, 1892.		
<p>I begin at cor. to secs. 23, 24, 25 and 26, which is a fir, 15 ins. in dia., marked T 20 S S 24 on NE., R 11 W S 25 on SE., S 26 on SW., S 23 on NW. sides, with 2 notches on S. and 1 notch on E. sides; from which</p> <p style="padding-left: 40px;">A fir, 12 ins. dia., bears N.55°E., 12 lks. dist., marked T 20 S R 11 W S 24 B T.</p> <p style="padding-left: 40px;">An alder, 9 ins. dia., bears S.2½°E., 193 lks. dist., marked T 20 S R 11 W S 25 B T.</p> <p style="padding-left: 40px;">An alder, 4 ins. dia., bears S.2°W., 223 lks. dist., marked T 20 S R 11 W S 26 B T.</p> <p style="padding-left: 40px;">An alder, 8 ins. dia., bears N.64°W., 54 lks. dist., marked T 20 S R 11 W S 23 B T.</p> <p>Thence I run</p> <p style="padding-left: 40px;">N.0°1'W., bet. secs. 23 & 24.</p> <p style="text-align: right; padding-right: 40px;">Var.20°19'E.</p> <p>Ascend.</p>		
3.25	Top of spur, bears E. & W.; descend.	+200
5.75	A gulch, course W.; ascend.	-60
8.75	Top of spur, bears E. & W.; descend.	+80
13.75	A gulch, course W.; ascend.	-200
23.90	Top of ridge, bears E. & W.; descend.	+350
27.50	A canyon, course W.; ascend.	-200
34.20	Top of ridge, bears E. & W.; descend.	+250
40.00	Set a post, 3 ft. long, 3 ins. sq., 18 ins. in the ground, for ¼ sec. cor., marked ¼ S on W. face; from which	
	A cedar, 10 ins. dia., bears N.12°E., 44 lks. dist., marked ¼ S B T.	
	A vine maple, 3 ins. dia., bears S.80°W., 42 lks. dist., marked ¼ S B T.	