

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 11 W.

CHAINS

	N.0°2'W., bet. secs. 22 & 23.	
	Var.20°20'E.	
1.08	A creek, 30 lks. wide, course SE.	
2.00	Leave bottom; begin ascent of W. slope.	
4.50	A side gulch, course W.; ascend S. slope & W. slope.	
12.00	A canyon, course SW.	
14.00	A canyon, course SW.; ascend E. slope.	
21.20	Top of ascent; steep descent of W. slope.	+250
26.75	A canyon, course W.	
29.10	Top of spur, bears E. & W.; steep descent.	+100
31.75	A branch, 2 lks. wide, in a canyon, course SW.	-60
37.00	Top of spur, bears E. & W.; a rocky steep ascent.	+80
40.00	An alder, 3 ins. dia., which I marked $\frac{1}{4}$ S on W. face, for $\frac{1}{4}$ sec. cor.; from which An alder, 3 ins. dia., bears S.5°W., 38 lks. dist., marked $\frac{1}{4}$ S B T. An alder, 2 ins. dia., bears S.40°E., 96 lks. dist., marked $\frac{1}{4}$ S B T.	
40.50	A canyon, course W.; ascend W. slope.	
43.00	Top of spur, bears E. & W.; along edge of a windfall, bears W.	+80
52.25	Top of spur, bears E. & W.; descend on W. slope, covered by alders.	+400
65.50	Top of dividing ridge; descend.	+300
68.75	A canyon, course W.	-100
73.60	Top of spur, bears E. & W.; very steep descent of NE. slope.	+80
79.00	A branch, 3 lks. wide, course NW.	-250
80.00	Set post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. to secs. 14, 15, 22 and 23, marked T 20 S S 14 on NE., R 11 W S 23 on SE., S 22 on SW., S 15 on NW. face, with 3 notches on S. and 2 notches on E. edges; from which A fir, 30 ins. dia., bears N.85°E., 19 lks. dist., marked T 20 S R 11 W S 14 B T.	+40