

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 11 W.

CHAINS

W S 34 on SE., S 33 on SW., S 28 on NW. faces, with 1 notch on S. and 3 notches on E. edges; from which

An alder, 18 ins. dia., bears N.50°E., 66 lks. dist., marked T 20 S R 11 W S 27 B T.

A vine maple, 4 ins. dia., bears S.32°W., 13 lks. dist., marked T 20 S R 11 W S 33 B T.

An alder, 24 ins. dia., bears S.60°E., 6 lks. dist., marked T 20 S R 11 W S 34 B T.

An alder, 14 ins. dia., bears N.83°W., 20 lks. dist., marked T 20 S R 11 W S 28 B T.

I run thence

N.0°2'W., bet. secs. 27 & 28.

Va.20°20'E.

Slightly descending through an alder flat, bears E. & W.

- | | | |
|-------|---|------|
| 17.20 | A canyon, course SE.; ascend. | -150 |
| 23.50 | Top of spur, bears SE. & NW.; begin steep descent. | +100 |
| 31.75 | A canyon, course SE.; ascend. | |
| 40.00 | Set a post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which
An alder, 4 ins. dia., bears N.27°E., 27 lks. dist., marked $\frac{1}{4}$ S B T.
An alder, 3 ins. dia., bears S.49°W., 15 lks. dist., marked $\frac{1}{4}$ S B T. | |
| | Keep ascending. | |
| 46.50 | Top of spur, bears E. & W.; descend. | +150 |
| 67.25 | A branch, 3 lks. wide, course SE.; ascend. | -120 |
| 73.75 | Top of ascent. | +80 |
| 80.00 | A fir, 15 ins., which I marked T 20 S S 22 on NE., R 11 W S 27 on SE., S 28 on SW., S 21 on NW. sides, with 2 notches on S. and 3 notches on E. sides, for cor. to secs. 21, 22, 27 & 28; from which
A fir, 24 ins. dia., bears N.65°E., 25 lks. dist., marked T 20 S R 11 W S 22 B T.
A cedar, 15 ins. dia., bears S.68 $\frac{1}{2}$ °E., 31 lks. dist., marked T 20 S R 11 W S 27 B T. | |