

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 11 W.

CHAINS		
5.50	A canyon, course W.	
7.32	A fir, 50 ins. dia., which I marked with 2 notches on N. & S. sides.	
27.50	Top of ridge, bears E. & W.; descend.	+350
31.75	A canyon, course E.; ascend.	-120
34.25	Top of spur, bears E. & W.; descend.	+100
35.75	A canyon, course E.; ascend.	-75
39.00	Top of ridge, bears E. & W.	+150
40.00	A fir, 50 ins. dia., which I marked $\frac{1}{4}$ S on W. side, for $\frac{1}{4}$ sec. cor.; from which A hemlock, 8 ins. dia., bears S.75°E., 3 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 36 ins. dia., bears N.3°W., 55 lks. dist., marked $\frac{1}{4}$ S B T.	
41.25	A canyon, course NE.; ascend.	-85
45.00	Top of spur, bears NE. & SW.; descend.	+100
47.25	A canyon, course NE.; ascend.	-75
53.00	Top of spur, bears NE. & SW.; descend.	+60
59.00	A creek, 6 lks. wide, course NW.	-150
61.50	A gulch, course SW.; begin ascent.	
67.50	Enter a timber flat, bears E. & W.	+175
69.00	A trail from Smiths River to 5 Mile Lake, bears N.10°W. & S.10°E.	
70.50	Leave flat.	
74.75	Top of flat ridge, bears E. & W.	+125
77.75	Begin descent.	
80.00	Set a post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. to secs. 15, 16, 21 and 22, marked T 20 S S 15 on NE., R 11 W S 22 on SE., S 21 on SW., S 16 on NW. face, with 3 notches on E. & S. edges; from which An elder, 4 ins. dia., bears N.2°E., 20 lks. dist., marked T 20 S R 11 W S 15 B T. An elder, 10 ins. dia., bears S.84°E., 32 lks. dist., marked T 20 S R 11 W S 22 B T. A fir, 48 ins. dia., bears S.63 $\frac{1}{2}$ °W., 7 lks. dist.,	-50