

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 11 W.

CHAINS	<p>marked T 20 S R 11 W S 21 B T. An alder, 8 ins. dia., bears N.88°W., 51 lks. dist., marked T 20 S R 11 W S 16 B T. May 17th, 1892.</p>	
	<p>N.89°41'E., on random line, bet. secs. 15 & 22. Var.20°20'E.</p>	
40.00	Set temp. $\frac{1}{4}$ sec. cor.	
80.76	Intersect N. & S. line, 40 lks. N. of cor. to secs. 14, 15, 22 & 23. Thence I run S.89°58'W., on true line, bet. secs. 15 & 22. Var.20°14'E.	
	Along N. slope of mountain, near the top.	
15.25	A canyon, course N.; ascend.	-80
40.38	Set a post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. side; from which A hemlock, 3 in. dia., bears S.65 $\frac{1}{2}$ °E., 37 lks. dist., marked $\frac{1}{4}$ S B T. An alder, 4 ins. dia., bears N.54°W., 85 lks. dist., marked $\frac{1}{4}$ S B T.	
53.75	A canyon, course N.	-75
74.25	A canyon, course N.	-60
80.76	The cor. to secs. 15, 16, 21 & 22.	
	<p>N.0°2'W., bet. secs. 15 and 16. Var.20°12'E.</p>	
	Descend E. slope.	
3.00	A canyon, course E.; ascend.	-100
5.50	Top of spur, bears E. & W.	+60
8.75	Top of ridge, bears NE. & SW.; descend W. slope.	+80
29.75	A canyon, course NW.	-200
40.00	A hemlock, 5 ins. dia., which I marked $\frac{1}{4}$ S on W. side, for $\frac{1}{4}$ sec. cor.; from which A fir, 30 ins. dia., bears S.55 $\frac{1}{2}$ °E., 9 lks. dist.,	