

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 11 W.

CHAINS		
	marked $\frac{1}{4}$ S B T.	
	A fir, 24 ins. dia., bears S. $20\frac{1}{2}^{\circ}$ W., 13 lks. dist.,	
	marked $\frac{1}{4}$ S B T.	
	Descend.	
49.50	Enter bottom, bears SE. & NW.	
51.10	A creek, 25 lks. wide, course NW.	
54.00	Leave bottom; begin ascent.	
	May the 18th.	
57.00	Top of ascent; descend.	+75
59.75	A creek, 5 lks. wide, course SW.; begin gradual ascent.	-60
79.50	Top of ridge, bears E. & W.	+400
80.00	Set a post, $4\frac{1}{2}$ ft. long, 4 ins. sq., 24 ins. in the ground, for cor. to secs. 15, 16, 10 & 9, marked T 20 S S 10 on NE., R 11 W S 15 on SE., S 16 on SW., S 9 on NW. faces, with 4 notches on S. and 3 notches on E. edges; from which	
	An alder, 24 ins. dia., bears N. $76^{\circ}$ E., 21 lks. dist., marked T 20 S R 11 W S 10 B T.	
	An alder, 16 ins. dia., bears S. $27\frac{1}{2}^{\circ}$ E., 10 lks. dist., marked T 20 S R 11 W S 15 B T.	
	A hemlock, 8 ins. dia., bears S. $62^{\circ}$ W., 15 lks. dist., marked T 20 S R 11 W S 16 B T.	
	An alder, 15 ins. dia., bears N. $20^{\circ}$ W., 15 lks. dist., marked T 20 S R 11 W S 9 B T.	
	N. $89^{\circ}58'E.$ , on true line, bet. secs. 10 & 15.	
	Var. $20^{\circ}15'E.$	
10.00	Leave ridge; begin descent of S. slope.	
20.75	A canyon, course S.; ascend.	-125
22.50	Top of spur, bears N. & S.; descend.	+60
24.50	A canyon, course S.; a gradual ascent.	-80
40.00	Set a post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{2}$ S on N. face; from which	
	An alder, 15 ins. dia., bears S. $69\frac{1}{2}^{\circ}$ E., 38 lks. dist., marked $\frac{1}{2}$ S B T.	