

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 11 W.

CHAINS

marked T. 20 S R 11 W S 3 B T.

A fir, 5 ins. dia., bears S.53°E., 114 lks. dist.,

marked T 20 S R 11 W S 10 B T.

A fir, 36 ins. dia., bears N.7°W., 95 lks. dist.,

marked T 20 S R 11 W S 4 B T.

A chittem, 3 ins. dia., bears S.52°W., 5 lks. dist.,

marked T 20 S R 11 W S 9 B T.

May 19th, 1892.

From the cor. of secs. 3, 4, 9, and 10, I run N.89°58'E., on a random line, bet. secs. 3 & 10, 2 & 11,

and 1 & 12, with a mean var. of 20°15'E. I set temp.

half mile and mile corx. at each 40 and 80 chs. and

find the line to be 3 miles, 2 chains, and 10 lks.

long, and the falling to be 120 lks. N. of cor. to secs.

1, 12, 6 & 7. The correction for the true line will,

therefore, be 40 lks. south and 70 lks. east for each

mile.

May 21st.

From the cor. to secs. 1 & 12, Tp. 20 S., R. 11 W. and

Secs. 6 & 7, R. 10 W., I run

N.89°45'W., on true line, bet. secs. 1 & 12.

Var.20°20'E.

Descend into

- .50 A canyon, course N.85°E.; ascend same. -10
- 6.50 Leave canyon; ascend N. slope.
- 23.50 Top of ridge, bears SE. & NW.; descend along S. slope. +300
- 40.35 Set a sandstone, 9x8x7 ins., 6 ins. in the ground, for -100
  - ¼ sec. cor., marked ¼ on S. face; and raised a mound
  - of stone, 1½ ft. high and 2 ft. base, alongside. Pits
  - impracticable.
- 46.00 Top of spur, bears N. & S.; descend. +150
- 53.50 A canyon, course S.; ascend. -80
- 76.00 Top of spur, bears N. & S.; descend. +120
- 79.00 A canyon, course S.; ascend. -100