

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 11 W.

CHAINS

marked T 19 S. R 11 W S 35 B T.

A cedar, 36 ins. diam., bears S.75 $\frac{1}{2}$ °E., 110 lks. dist.,

marked T 20 S R 11 W S 2 B T.

A cedar, 36 ins. dia., bears S.88°W., 246 lks. dist.,

marked T 20 S R 11 W S 3 B T.

Thence I run

S.0°14'W., on true line, bet. secs. 2 & 3.

Var.20°14'E.

Descend.

4.00	Enter bottom, bears E. & W.	
4.50	Fiddle Creek, 40 lks. wide, course W.	
9.50	Leave bottom; begin ascent.	
16.50	Top of spur, bears NW. & SE.; descend SW. slope.	+85
21.30	A canyon, course NW.; ascend NE. slope.	-70
38.00	Top of spur, bears NW. and SE.	+160
45.70	Top of spur, bears W. & E.	+60
48.60	Set a post, 3 ft. long, 3 ins. square, 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which	
	A willow, 4 ins. dia., bears N.12°W., 39 lks. dist.,	
	marked $\frac{1}{4}$ S B T.	
	A cedar, 24 ins. dia., bears S.27°E., 15 lks. dist.,	
	marked $\frac{1}{4}$ S B T.	
51.25	Top of ridge, bears E. & W.; begin steep descent.	+80
58.70	Top of spur, bears SE. & NW.; descend.	-60
65.75	A canyon, course SW.; ascend.	-120
71.25	Top of spur, bears SW. & NE.; descend.	+60
76.75	A canyon, course SE.; ascend E. slope.	-50
79.00	Top of spur, bears E. & W.	+40
80.25	Enter small bottom, bears E. & W.	
82.00	A creek, 15 lks. wide, course NW.; ascend NW. slope.	
85.25	Top of ascent.	+60
88.60	The cor. to secs. 2, 3, 10 & 11.	

N.89°45'W., on true line, bet. secs. 3 & 10.