

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 11 W.

CHAINS
80.64

The cor. to secs. 20, 21, 28 & 29.

May 28th, 1892.

N.0°3'W., bet. secs. 20 & 21.

Var.20°20'E.

0.50	A branch, 3 lks. wide, course W.; ascend.	-20
6.50	Top of spur, bears NW. & SE.; descend.	+220
27.00	A branch, 5 lks. wide, course SW.	-220
38.50	Top of spur, bears SW. & NE.; descend.	+180
40.00	Set a post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which A maple, 4 ins. dia., bears N.33°W., 41 lks. dist., marked $\frac{1}{4}$ S B T. A maple, 3 ins. dia., bears S.87°E., 64 lks. dist., marked $\frac{1}{4}$ S B T.	
47.25	A canyon, course SW.; ascend.	-150
52.50	Top of spur, bears SW. & NE.	+120
57.25	A canyon, course SW.; ascend.	-100
61.00	Top of ridge, bears E. & W.; descend.	+180
66.50	A canyon, course NE.; ascend.	-80
71.25	Top of spur, bears E. & W.	+60
77.50	A canyon, bears NE.; ascend.	-50
79.50	Top of spur, bears NE. & SW.	+40
80.00	Set a post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. to secs. 16, 17, 20 & 21, marked T 20 S S 16 on NE., R 11 W S 21 on SE., S 20 on SW., S 17 on NW. faces, with 3 notches on S. and 4 notches on E. edges; from which A spruce, 12 ins. dia., bears N.26°E., 63 lks. dist., marked T 20 S R 11 W S 16 B T. A fir, 36 ins. dia., bears S.46°E., 28 lks. dist., marked T 20 S R 11 W S 21 B T. A vine maple, 4 ins. dia., bears S.20°W., 30 lks. dist., marked T 20 S R 11 W S 20 B T. A vine maple, 4 ins. dia., bears N.44°W., 24 lks. dist., marked T 20 S R 11 W S 17 B T.	-25