

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 11 W.

CHAINS		
16.50	A canyon, course NE.; ascend.	-225
22.50	Top of spur, bears NE. & SW.	-175
28.50	A canyon, course NE.; ascend.	-200
31.00	Top of spur, bears NE. & SW.; descend.	+50
36.75	A canyon, course NE.	-100
38.10	A canyon, course E.	
40.00	An alder, 6 ins. dia., which I marked $\frac{1}{4}$ S on W. face, for $\frac{1}{4}$ sec. cor.; from which An alder, 8 ins. dia., bears N.80 $\frac{1}{2}$ °E., 20 lks. dist., marked $\frac{1}{4}$ S B T. An alder, 8 ins. dia., bears N.83°W., 39 lks. dist., marked $\frac{1}{4}$ S B T.	
44.25	Top of ridge, bears NE. & SW.	+175
52.60	A canyon, course NE.; ascend.	-200
62.50	Top of spur, bears NE. & SW.; descend NW. slope.	+175
70.25	A canyon, course NE.	-200
75.50	Top of spur, bears E. & W.	+40
78.50	Foot of hill; enter bottom, bears NW. and SE.	-50
80.00	Set a post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. to secs. 8, 9, 16 & 17, marked T 20 S S 9 on NE., R 11 W S 16 on SE., S 17 on SW., S 8 on NW. faces, with 4 notches on E. & S. edges; from which A fir, 50 ins. dia., bears N.11 $\frac{1}{2}$ °E., 480 lks. dist., marked T 20 S R 11 W S 9 B T. An alder, 10 ins. dia., bears S.2°E., 205 lks. dist., marked T 20 S R 11 W S 16 B T. A cedar, 30 ins. dia., bears S.41°W., 217 lks. dist., marked T 20 S R 11 W S 17 B T. A maple, 15 ins. dia., bears N.89°W., 13.25 chs. dist., marked T 20 S R 11 W S 8 B T. May 30, 1892.	

N.89°42'E., on random line, bet. secs. 9 & 16.

Var. 20°20'E.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.36 Intersect N. & S. line, 45 lks. N. of cor. to secs. 15,