

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 11 W.

CHAINS		
37.25	Top of spur, bears E. & W.	+150
40.00	Set a post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which A fir, 8 ins. diam., bears S.74°W., 7 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 6 ins. dia., bears S.42°E., 11 lks. dist., marked $\frac{1}{4}$ S B T.	
41.00	Top of spur, bears E. & W.; descend.	+25
45.00	A canyon, course E.; ascend.	-75
46.50	Top of ascent; descend.	+40
49.50	A canyon, course E.	-50
56.50	A creek, course S.30°E., 5 lks. wide.	-40
59.25	Top of spur, E. & W.; descend.	-75
68.00	A canyon, course SE.; ascend.	-100
74.50	Top of spur, bears E. & W.; descend.	+120
77.00	A canyon, course E.; ascend.	-75
79.00	Top of spur, bears E. & W.	+90
80.00	Set a post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. to secs. 4, 5, 8 & 9, marked T 20 S S 4 on NE., R 11 W S 9 on SE., S 8 on SW., S 5 on NW. faces, with 5 notches on S. & 4 notches on E. edges; from which A cedar, 10 ins. dia., bears N.87°E., 127 lks. dist., marked T 20 S R 11 W S 4 B T. A vine maple, 4 ins. dia., bears S.17°E., 50 lks. dist., marked T 20 S R 11 W S 9 B T. A fir, 15 ins. dia., bears S.73°W., 3 lks. dist., marked T 20 S R 11 W S 8 B T. A cedar, 36 ins. dia., bears N.27°W., 100 lks. dist., marked T 20 S R 11 W S 5 B T.	

June 1st, 1892.

S.89°59'E., on random line, bet. secs. 4 & 9.

Var. 20°20'E.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.56 Intersect N. & S. line, 48 lks. N. of cor. to secs. 3, 4,