

Subdivisions of T. 20 S., R. 11 W.

CHAINS		
	Var. 20° 10' E.	
.50	Top of spur, bears N. & S.; descend.	+25
1.50	A dry canyon, course S.	-45
3.00	Top of spur, bears N. & S.	+50
10.00	Top of ridge, bears NE. & SW.; begin descent of N. slope.	+80
24.50	Top of spur, bears NW. & SE.	-120
32.00	Enter bottom, bears NE. & SW.	-160
33.60	A creek, 25 lks. wide, course SW.	
35.50	Leave bottom; begin ascent.	
40.00	Set a post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which A spruce, 40 ins. diam., bears N. 66 $\frac{1}{2}$ ° W., 21 lks. dist., marked $\frac{1}{4}$ S B. T. An alder, 15 ins. diam., bears S. 12° W., 21 lks. dist., marked $\frac{1}{4}$ S B. T.	
48.00	Top of flat spur, bears N. & S.	+150
54.00	Begin descent.	
56.50	A canyon, course S.; ascend.	-75
57.50	Top of spur, bears N. & S.; descend.	+50
64.75	A canyon, course S.; ascend.	-100
73.50	Top of spur, bears N. & S.; descend.	+150
77.90	Intersect west boundary of township, 310 lks. S. of cor. to secs. 30, 31, 36 & 25, which is a post, 4 ins. square, pretty well decayed, marked T 20 S S 30 on NE., R 11 W S 31 on SE., R 12 W S 36 on SW., S 25 on NW. faces, with 1 notch on S. and 5 notches on N. edges; from which A spruce, 30 ins. diam., bears N. 18° E., 54 lks. dist., marked T 20 S R 11 W S 30 B T. An alder, 24 ins. diam., bears S. 40° E., 8 lks. dist., marked T 20 S R 11 W S 31 B T. A spruce, 6 ins. diam., bears S. 86° W., 90 lks. dist., marked T 20 S R 12 W S 36 B T.	