

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 11 W.

CHAINS

A spruce, 48 ins. diam., bears N.7°W., 25 lks. dist.,
marked T 20 S R 12 W S 25 B T.

At point of intersection I set a closing cor. to secs. 30
& 31 by setting a post, 4½ ft. long, 4 ins. square, 24
ins. in the ground, marked S 30 on N., C C T 20 S R 11
W on E., S 31 on S. faces, with 1 notch on S. and 5
notches on N. faces; from which

An alder, 15 ins. diam., bears N.55½°E., 24 lks. .
dist., marked T 20 S R 11 W S 30 B T.

A fir, 15 ins. diam., bears S.66°E., 4 lks. dist.,
marked T 20 S R 11 W S 31 B T.

A fir, 18 ins. diam., bears N.25°W., 18 lks. dist.,
marked T 20 S R 11 W C C S 30 & 31 B T.

Land, mountainous, 74.40 chs.

Soil, gravelly & 3rd rate, except about 3.50 chs. east
of ¼ sec. cor., which is alluvial bottom & 1st rate.

Heavily timbered with fir, spruce, hemlock, alder, cedar,
maple, chitten.

Dense undergrowth of salmon, salal, and thimbleberries
& vine maples, 77.90 chs.

June 5th, 1892.

N.0°4'W., between secs. 29 & 30.

Var. 20°20'E.

5.00	Top of ridge, bears E. & W.; descend.	+125
11.50	Top of spur, bears SE. & NW.; descend.	-70
18.00	A canyon, course W.; ascend.	-120
20.50	Top of spur, bears E. & W.; descend.	+50
23.50	A canyon, course W.; ascend.	-45
30.50	Top of flat spur, bears E. & W.	+120
34.50	Top of spur, bears E. & W.; descend.	+30
37.50	A canyon, course W.	-25
40.00	Set a post, 3 ft. long, 3 ins. sq., 24 ins. in the ground,	