

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 11 W.

CHAINS		
40.00	Set temp. $\frac{1}{4}$ sec. cor.	
80.74	Intersect N. & S. line, 42 lks. N. of cor. of secs. 20, 21, 28, and 29.	
	June 7th, 1892.	
	Thence I run	
	N.89°57'W., on true line, bet. secs. 20 & 29.	
	Var.20°20'E.	
	Descend.	
4.00	A branch, 3 lks. wide, course N.; ascend.	-100
8.00	Top of spur, bears N. & S.; steep descent.	+200
14.00	A canyon, course N.; steep ascent.	-400
19.00	Top of spur, bears N. & S.; very steep descent.	+200
28.50	A canyon, course N.; ascend.	-400
33.50	Top of ascent; begin descent.	+50
38.75	Enter bottom, bears N. & S.	-120
39.25	A creek, 10 lks. wide, course S.	
40.37	Set a post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which A maple, 6 ins. diam., bears N.9°E., 7 lks. dist., marked $\frac{1}{4}$ S B T. A leaning maple, 7 ins. diam., bears S.34°W., 8 lks. dist., marked $\frac{1}{4}$ S B T.	
	Leave bottom.	
47.50	A canyon, course S.; ascend NE. slope,	
56.25	Top of spur, bears N. & S.; descend.	+300
71.25	A branch, 3 lks. wide, course S., at the foot of a big slide, a lake above; begin steep ascent.	-400
78.00	Top of spur, bears N. & S.	+250
80.74	The cor. to secs. 19, 20, 29 & 30.	
	West, on true line, bet. secs. 19 & 30.	
	Var.20°10'E.	
5.75	A canyon, course S.; ascend.	-180
10.00	Top of spur, bears N. & S.; descend.	+120
23.25	A canyon, course SE.; ascend.	-75