

Subdivisions of T. 20 S., R. 11 W.

CHAINS		
31.50	Top of ridge, bears NE. & SW.	+150
40.00	Set a post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which An alder, 24 ins. dia., bears S.46 $\frac{1}{2}$ °E., 23 lks. dist., marked $\frac{1}{4}$ S B T. A spruce, 8 ins. dia., bears N.34°E., 16 lks. dist., marked $\frac{1}{4}$ S B T.	
43.50	A canyon, course NW.; ascend.	-75
50.75	Top of spur, bears N. & S.; descend.	+85
66.25	A canyon, course SW.; ascend.	-100
73.00	Top of spur, bears NE. & SW.; descend N. slope.	-120
78.02	Intersect West bdy. of Tp., 3.40 chs. S. of cor. to secs. 19, 30, 25 and 24, which is a decayed post, 4 ins. sq., marked T 20 S S 19 on NE., R 11 W S 30 on SE., R 12 W S 25 on SW., S 24 on NW. face, with 2 notches on S. and 4 notches on N. edges; from which A spruce, 40 ins. dia., bears N.15°E., 38 lks. dist., marked T 20 S R 11 W S 19 B T. A spruce, 24 ins. dia., bears S.35°E., 58 lks. dist., marked T 20 S R 11 W S 30 B T. A spruce, 3 ins. dia., bears S.25°W., 70 lks. dist., marked T 20 S R 12 W S 25 B T. A spruce, 36 ins. dia., bears N.48°W., 35 lks. dist., marked T 20 S R 12 W S 24 B T. At point of intersection I set a post, 4 $\frac{1}{2}$ ft. long, 4 ins. sq., 24 ins. in the ground, for closing cor. to secs. 19 and 30, marked S 19 on N., C C T 20 S R 11 W on E., S 30 on S. faces, with 2 notches on S. and 4 notches on N. faces; from which A spruce, 18 ins. dia., bears N.44°E., 33 lks. dist., marked T 20 S R 11 W S 19 B T. A hemlock, 8 ins. dia., bears S.66 $\frac{1}{2}$ °E., 32 lks. dist., marked T 20 S R 11 W S 30 B T. A hemlock, 20 ins. dia., bears S.80°W., 22 lks. dist., marked T 20 S R 11 W C C S 30 & 19 B T.	

June 8th, 1892.