

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 11 W.

CHAINS

	N.0°4'W., bet. secs. 19 & 20.	
	Var.20°20'E.	
	Ascend.	
5.00	Top of spur, bears SW. and NE.; begin descent of SE. slope.	+100
17.25	A canyon, course SE.; ascend.	-200
24.50	Top of spur, bears E. & W.	+120
38.25	A canyon, course E.	-100
40.00	Set a post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which An elder, 3 ins. dia., bears N.27°E., 17 lks. dist., marked $\frac{1}{4}$ S B T. An elder, 3 ins. dia., bears S.45°W., 12 lks. dist., marked $\frac{1}{4}$ S B T.	
47.00	Top of ridge, bears SW. and NE.	
56.00	A canyon, course W.; ascend.	-120
64.50	Top of spur, bears NW. and SE.; descend.	+150
79.70	A creek, 5 lks. wide, course W.	-125
80.00	Set a post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. to secs. 17, 18, 19 & 20, marked T 20 S S 17 on NE., R 11 W S 20 on SE., S 19 on SW., S 18 on NW. faces, with 3 notches on S. and 5 notches on E. edges; from which A spruce, 15 ins. dia., bears N.30°E., 76 lks. dist., marked T 20 S R 11 W S 17 B T. An alder, 30 ins. dia., bears S.89°E., 56 lks. dist., marked T 20 S R 11 W S 20 B T. An alder, 24 ins. dia., bears S.4°W., 79 lks. dist., marked T 20 S R 11 W S 19 B T. An alder, 30 ins. dia., bears N.87 $\frac{1}{2}$ °W., 46 lks. dist., marked T 20 S R 11 W S 18 B T.	

S.89°57'E., on random line, bet. secs. 17 & 20.

Var.20°10'E.

40.00	Set temp. $\frac{1}{4}$ sec. cor.	
80.22	Intersect N. & S. line, 45 lks. S. of cor. to secs. 16,	