

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 11 W.

CHAINS		
	ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which	-200
	A maple, 10 ins. dia., bears N.13°E., 15 lks. dist., marked $\frac{1}{4}$ S B T.	
	A fir, 40 ins. dia., bears S.1°W., 14 lks. dist., marked $\frac{1}{4}$ S B T.	
51.00	A canyon, course S.	-150
54.00	A canyon, course N.65°W.; ascend.	-25
60.00	Top of spur, bears N. & S.; descend.	+60
64.75	A canyon, course S.	-80
65.75	County road from 5 mile country to Gardner, bears SW. and NE.	

June 10th, 1892.

65.90 Top of bluff overlooking a marsh on line; said marsh is thickly covered by willows and by water from 1 to 3 feet in depth, impassable; I, therefore, set a post; from which

 An alder, 8 ins. dia., bears S.15°E., 5 lks. dist., marked with a blaze and notch on the NW. side, facing the post, and

 An alder, 10 ins. dia., bears N.15°E., 5 lks. dist., marked with a blaze and notch on the SW. side, facing the post;

thence run by traverse:

- N.34° E., 7.55 Chs.
- S.88° W., 7.30 "
- N.80 $\frac{1}{2}$ °W., 2.15 "
- S.36° W., 2.85 "
- S.70 $\frac{1}{2}$ °W., 1.50 "
- West 3.00 "
- South 3.55 "

77.19 Intersect West boundary of Tp., 355 lks. S. of cor. to secs. 18, 19, 13 & 24.

At point of intersection

I set a post, 4 $\frac{1}{2}$ ft. long, 4 ins. sq., 24 ins. in the