

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 11 W.

CHAINS

S S 8 on NE., R 11 W S 17 on SE., S 18 on SW., S 7 on NW. faces, with 4 notches on S. and 5 notches on E. edges; from which

An alder, 24 ins. dia., bears N.80°E., 72 lks. dist., marked T 20 S R 11 W S 8 B T.

An alder, 20 ins. dia., bears S.15½°E., 28 lks. dist., marked T 20 S R 11 W S 17 B T.

An alder, 18 ins. dia., bears S.79½°W., 70 lks. dist., marked T 20 S R 11 W S 18 B T.

An alder, 15 ins. dia., bears N.12°W., 69 lks. dist., marked T 20 S R 11 W S 7 B T.

N.89°44'E., on random line, bet. secs. 8 & 17.

Var.20°10'E.

40.00 Set temp. ¼ sec. cor.

80.10 Intersect N. & S. line, 46 lks. N. of cor. to secs. 8, 9, 16 & 17.

June 16th, 1892.

Thence I run

N.89°56'W., on true line, bet. secs. 17 & 8.

Var.20°20'E.

Through cleared bottom.

2.50 Five Mile Creek, 35 lks. wide, course NW.

12.25 Leave clearing; begin ascent.

20.25 Top of spur, bears N. & S.; descend. +150

25.00 A canyon, course NW.; ascend. -50

28.25 Top of spur, bears N. & S.; descend. +60

29.75 A canyon, course NW.; descend. -50

40.05 Set a post, 5 ft. long, 3 ins. sq., 24 ins. in the ground, for ¼ sec. cor., marked ¼ S on North face; from which A fir, 5 ins. dia., bears S.84½°W., 51 lks. dist., marked ¼ S B T.

A spruce, 12 in. dia., bears N.41°W., 50 lks. dist., marked ¼ S B T.

J. Gabriel's house bears N.45°E., about 3.00 chs. dist.