

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 11 W.

CHAINS		
59.25	Top of ridge, bears SE. & NW.	+200
62.50	Top of ridge, bears NE. & SW.; descend.	
76.65	Intersect West boundary of Tp., 305 lks. S. of cor. to secs. 7, 18, 12 & 13.	
	At point of intersection	
	I set a post for closing cor. to secs. 18 and 7, 4 ft. long, 4 ins. sq., 24 ins. in the ground, marked S 7 on N., C C T 20 S R 11 W on E., S 18 on S. faces, with 2 notches on N. and 4 notches on S. faces; from which	
	A spruce, 6 ins. dia., bears N.87°E., 165 lks. dist., marked T 20 S R 11 W S 7 B T.	
	A vine maple, 4 ins. dia., bears S.43°E., 36 lks. dist., marked T 20 S R 11 W S 18 B T.	
	An alder, 6 ins. dia., bears S.26°W., 37 lks. dist., marked T 20 S R 11 W C C S 7 & 18 B T.	
	June 17th, 1892.	

N.0°4'W., bet. secs. 7 & 8.

Var. 20°20'E.

Leave foot of hill; begin ascent through small alders.

5.50	Enter maple flat.	+100
9.50	Leave flat; begin ascent.	
15.00	Very steep ascent.	
17.00	Top of spur, bears SE. & NW.; along E. slope of same.	+200
24.50	Top of spur, bears E. & W.; descend.	+90
27.50	A canyon, course E.; ascend.	+40
34.25	Top of ridge, bears NE. & SW.; begin descent of W. slope.	+150
40.00	Set a post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for 1/2 sec. cor., marked 1/2 S B T on W. face; from which	
	A fir, 8 ins. dia., bears S.43 1/2°E., 12 lks. dist., marked 1/2 S B T.	
	An alder, 3 ins. dia., bears N.63°W., 7 lks. dist., marked 1/2 S B T.	
	Descend through small alders.	
50.50	Top of spur, bears E. & W.; descend.	