

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 11 W.

CHAINS

	marked $\frac{1}{4}$ S B T.	
	A fir, 36 ins. dia., bears S.13°W., 39 lks. dist.,	
	marked $\frac{1}{4}$ S B T.	
	Descend West slope of mountain.	
65.25	A gulch, course NW.	-400
69.00	Top of spur, bears NW. & SE.; descend.	+50
73.35	A gulch & branch, 4 lks. wide, course N.25°W.; ascend NE.	
	slope.	-60
78.00	Top of ascent.	+75
79.50	The cor. to secs. 5, 6, 7, & 8.	
<hr/>		
	West, on true line, bet. secs. 6 & 7.	
	Var. 19°40'E.	
	Descend.	
3.50	A canyon, course N.; ascend.	-100
6.75	Top of spur, bears N. & S.; descend.	+80
9.50	A canyon, course N.; ascend.	+90
14.00	Top of spur, bears N. & S.; descend.	+100
20.25	A canyon, course N.	-60
24.50	A canyon, course N.; ascend.	
26.50	Top of spur, bears N. & S.; descend.	+200
31.25	A gulch, course N.; ascend.	
32.00	Top of ascent; begin descent of N. slope of mountain.	
40.00	Set a post, 3 ft. long, 3 ins. sq., 24 ins. in the ground,	
	for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which	
	An alder, 10 ins. dia., bears N.1 $\frac{1}{2}$ °E., 9 lks. dist.,	
	marked $\frac{1}{4}$ S B T.	
	A hemlock, 10 ins. dia., bears S.9 $\frac{1}{2}$ °E., 23 lks. dist.,	
	marked $\frac{1}{4}$ S B T.	
41.85	Fir, 36 ins. dia., which I marked with 2 notches on E. &	
	W. sides. This fir stands near foot of hill, from	
	whence a marsh, covered by water and impassable, reaches	
	to the Ten Mile Lake.	
	As I cannot from the foot of this tree see the edge of the	
	lake, a dense growth of timber and tall underbrush near	