

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 10 W.

CHAINS

An alder, 3 in. dia., bears N.70°W., 3 lks. dist.

An alder, 5 in. dia., bears N.45°E., 7 lks. dist.

80.00 Set stone, 17x12x4, for corner to secs. 26, 27, 34 & 35;  
from which

A chitterwood, 6 in. dia., bears N.55°E., 33 lks. dist.  
Feb. 8th.

East, between secs. 26 & 35.

Va.19°East.

Ascend hill.

40.00 Set stone, 16x14x7, for  $\frac{1}{2}$  sec. cor.; from which

A fir, 48 in. dia., bears S.40°E., 33 lks. dist.

72.50 Brook, 8 lks. wide, runs South.

80.00 Set post for corner to secs. 25, 26, 35 & 36; from which +300

A fir, 30 in. dia., bears N.50°E., 20 lks. dist.

A fir, 4 in. dia., bears S.67°E., 26 lks. dist.

A vine maple, 3 in. dia., bears S.50°W., 21 lks. dist.

A vine maple, 5 in. dia., bears N.42°W., 26 lks. dist.

South between secs. 35 & 36.

Va.19°East.

Descend hill.

18.00 Smiths River, 100 lks. wide, runs West. -300

Note: This point on Smiths River is above tide water and  
is not navigable for rafts or small boats. I here inter-  
sect high rugged mountains.

Feb. 9th.

East between secs. 25 & 36.

Va.19°East.

13.10 Creek, 10 lks. wide, runs South.

I here intersect rough rugged mountains, inaccessible to  
survey.

North between secs. 33 & 34.

Va.19°East.