

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 10 W.

CHAINS

A vine maple, 6 ins. dia., bears S.5°E., 58 lks. dist.
 A vine maple, 4 ins. dia., bears N.87°W., 70 lks.
 dist.

80.00 The corner to secs. 27, 28, 33 & 34.

Feb. 10th, 1867.

 North between secs. 27 & 28.

Var. 19° East.

2.65 Smiths River, 234 lks. wide, runs West. Set meander post on left bank; from which

A maple, 24 in. dia., bears S.50°W., 6 lks. dist.

An alder, 15 ins. dia., bears S.55°E., 48 lks. dist.

5.00 Set meander post on right bank; from which

A maple, 15 in. dia., bears S.75°W., 33 lks. dist.

A vine maple, 5 ins. dia., bears N.75°E., 36 lks.
dist.40.00 Set post for $\frac{1}{4}$ sec. corner; from which

An alder, 15 in. dia., bears S.7°W., 117 lks. dist.

An alder, 18 in. dia., bears S.45°E., 10 lks. dist.

Note: I intersect steep rugged mountains, impracticable to survey.

 North between secs. 32 & 33.

Ascend hill.

40.00 Set stone, 24x14x6 ins., for $\frac{1}{4}$ sec. corner; from which

A fir, 30 in. dia., bears N.45°W., 12 lks. dist.

80.00 Set stone, 20x10x8, for corner to secs. 28, 29, 32 & 33; +400
from which

An alder, 20 in. dia., bears N.82°W., 34 lks. dist.

 East, on a random line, between secs. 28 & 33.
40.00 Set temporary $\frac{1}{4}$ sec. post.79.80 Intersect N. & S. line, 36 lks. South of corner to secs.
27, 28, 33 & 34; from which I run

S.89°45'W., on a true line, between secs. 28 & 33.