

Subdivisions and East Bdy. of T. 20 S., R. 10 W.
 Survey by W. H. Byars under Contract No. 202 dated March
 11th, 1874.

CHAINS

Beginning at the corner to Secs. 25, 26, 35 & 36 and run
 East, on a true line, between secs. 25 & 36.

Variation 19°E.

- 9.50 Top of spur, c S. +200
- 13.25 A creek bed, 25 lks. wide, c S. -50
- 40.00 Set a fir post, 36 in. long, 5 in. dia., 18 ins. in
 ground, for $\frac{1}{2}$ sec. corner; from which
 A double maple, 60 in. dia., bears S.50°E., dist. 8
 lks.
 A double maple, 20 in. dia., bears N.18°W., 40 lks.
 dist.
- 53.00 A creek, 3 lks. wide, c S. -50
- 77.25 A creek, 5 lks. wide, c SW. "
- 80.00 Set an alder post, 36 ins. long, 5 ins. diam., 18 ins. in
 ground, for corner to secs. 25, 30, 31 & 36; from which
 An alder, 20 in. diam., bears N.52°E., dist. 75 lks.
 A cedar, 72 in. diam., bears S.60°E., dist. 30 lks.
 An alder, 24 ins. dia., bears S.85°W., 13 lks. dist.
 A hemlock, 20 in. diam., bears N.50°W., dist. 28 lks.

From the cor. to secs. 25, 30, 31 & 36, on the East
 boundary of the Tp., I run

South on true line on E. bdy. of Sec. 36.

Variation 19°E.

- 29.00 Deep gulch; steep hill to south. -500
- Marked chitterwood, 5 in. diam., for witness corner, said
 tree stands on large log over gulch. No witness trees.
 Aug. 11th, 1874.

Beginning at the established corner to sections 19, 20,
 29 & 30; thence

West, on true line, between secs. 19 & 30.

Variation 20°E.

- 8.00 A creek, 15 lks. wide, c NW. -50
- 17.00 Begin steep descent.