

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 10 W.

CHAINS

21.00 Enter valley. -300

29.50 North Smiths River, c S.  
Across; base South 1.00 ch.; angle opposite 34°, distance over 1.37 chs.

30.87 To right bank of river.

31.50 Begin ascent.

40.00 Set a chitterwood post, 40 in. long, 5 in. diam., 18 in. in ground, for  $\frac{1}{4}$  sec. cor.; from which  
A fir, 20 in. dia., bears N.52°W., dist. 29 lks.  
A chitterwood, 4 in. dia., bears S.50°E., dist. 30 lks.  
Aug. 12th, 1874.

Begin at cor. to secs. 19, 20, 29 & 30,  
East, on true line, between secs. 20 & 29.  
Variation 20°E.

10.75 A creek, 3 lks. wide, c N. -50

13.50 A creek, 3 lks. wide, c N. "

18.00 Begin steep ascent.

20.00 Marked a cherry, 6 in. diam., for witness corner.

Begin at the corner to sections 19, 20, 29 & 30,  
North, on true line, between secs. 19 & 20.  
Variation 20°E.

6.00 Begin descent.

8.00 Enter valley, c SW. & NE. -300

10.00 Smiths River, c SW., 75 lks. wide. Chained across by aid of boat.

11.50 Enter clearing, follows river.

27.00 Leave clearing; begin ascent.

33.00 Top of spur, c NE. +250

40.00 Set a maple post, 40 in. long, 5 ins. dia., for the  $\frac{1}{4}$  sec. cor.; from which  
A maple, 20 in. dia., bears N.46°E., dist. 6 lks.  
An alder, 8 in. dia., bears N.40°W., dist. 13 lks.

52.50 A creek, 30 lks. wide, c E.