

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 10 W.

CHAINS

A fir, 5 in. diam., bears S.40°W., dist. 76 lks.

An alder, 5 in. diam., bears N.35°W., dist. 19 lks.

East, on true line, between secs. 8 & 17.

Variation 20°E.

7.00	Enter valley, c NE. & SW.	-300
10.50	Smiths River; 75 lks. wide, c SE.	
18.50	Intersect river, from NE. to N.60°W.	
19.25	Leave same.	
20.00	A large stone projecting from ground two feet; drove alder post, 36 in. long, 4 ins. dia., by side of stone, for witness corner; from which	
	An alder, 7 in. diam., bears North, dist. 16 lks.	
	Aug. 14th, 1874.	

West Bdy. of T. 20 S., R. 9 W.

Survey by Wm. Thiel under Contract 260 dated Apr. 17, 1877.

Commence at corner to secs. 25, 30, 31 and 36, Townships 20 South, Ranges 9 and 10 West. Post still standing; from which

An alder, 20 in. dia., bears N.52°E., 75 lks. dist.

A cedar, 72 in. dia., bears S.60°E., 30 lks. dist.

An alder, 24 in. dia., bears S.85°W., 13 lks. dist.

A hemlock, 20 in. dia., bears N.50°W., 28 lks. dist.

agreeably to field notes furnished me.

Thence on West boundary of Township 20 S., R. 9 W.

South on West boundary of Sec. 31.

Latitude 43°44'. Var. 19½°E.

3.50	Top of spur, bears W. and E.	+60
7.50	Gulch, course SW.	-90
9.50	Top of spur, bears E. and W.	+60
17.75	Gulch, c SW.	+350
19.50	Top of spur.	-100
20.75	Gulch, c SW.; 1.00 ch. East is a large rock, 20 ft. high and 25 feet long.	-50