

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 10 W.
 Survey by Wm. Thiel under Contract 271 dated Aug. 18th, 1877.

CHAINS

I commence at the $\frac{1}{2}$ sec. post on line bet. secs. 17 and 20; from which

A maple, 8 in. dia., bears N.70°E., 24 lks.

A maple, 40 in. dia., bears S.40°W., 15 lks.

in conformity with the field notes issued from your office.

Thence I run

East, on true line, between secs. 17 and 20.

Var.20°E.

41.55 Smiths River, course W.

42.30 Left bank of river.

+100

43.20 F. M. Johnson's house bears S., about 4.00 chs.

Enter bottom.

-5

45.10 Branch, 10 lks. wide, course SW.

54.00 Leave bottom; commence ascending.

64.25 Top of spur, course N.60°W. and S.60°E.

+300

67.50 Top of spur, course NW. and SE.; commence descent.

+25

75.00 Canyon, course NW.; commence ascending.

-100

77.50 Top of spur, course NW. and SE.; commence descent.

+150

80.00 Set post, in middle of flat gulch, for corner to sections 16, 17, 20 and 21; from which

-75

An alder, 15 in. in dia., bears N.17°W., 40 lks.dist.

A chitterwood, 6 in. in dia., bears S.84°W., 37 lks. dist.

A chitterwood, 8 in. in dia., bears N.21°E., 79 lks. dist.

A vine maple, 4 in.dia., bears S.50°E., 20 lks. dist.

Feb. 25, 1878.

Seeing that the improvements of and the land desired by applicant, lie in Sec. 20, I, by authority of your office, run thence

South, on line, between sections 20 and 21.

Var.20°East.

Commence ascending.

1.75 Top of spur, course N.75°E. and S.75°W.; keep ascending

+120