

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 10 W.

CHAINS		
34.50	Canyon, course N.; commence ascending.	-200
40.30	Set $\frac{1}{4}$ sec. post; from which	+100
	A fir, 48 in. in dia., bears N.5°E., 17 lks. dist.	
	A fir, 24 in. dia., bears S.19°W., 23 lks. dist.	
46.00	Gulch, course NW.; commence ascent.	-100
49.60	Top of spur, course N. and S.	+200
52.90	Canyon, course NW.; commence ascent.	-200
55.50	Top of spur; commence descending N. slope.	+150
63.00	Gulch, c S.; enter timber flat.	-120
80.60	Intersect post.	
	Feb. 27th, 1878.	
<p>From post set 20 chs. East of post to cor. of secs. 7, 8, 17 and 18; from which</p> <p> An alder, 7 in. in dia., bears N., 16 lks. dist. agreeably to field notes furnished by your office, I run</p> <p> East, on true line, between secs. 8 and 17.</p> <p> Var. 20° East.</p>		
20.00	Commence ascending steep bluff.	+25
20.50	Enter alder flat.	
25.40	Fir, 48 in. in dia.	
29.00	Leave flat, top of rise.	+60
31.25	Gulch, course N.30°W.	-40
38.00	Top of spur, course NW.	+60
40.00	Set $\frac{1}{4}$ sec. post; from which	
	A cherry, 5 in. in dia., bears S.34°E., 11 lks. dist.	
	A fir, 6 in. in dia., bears N.21°E., 17 lks. dist.	
42.50	Canyon, course NW.; commence ascending a rocky North slope.	-60
49.80	Georgia Creek, course NW., 10 lks. wide.	
59.50	Top of ridge, course N.60°E. and S.60°W.; thence on south slope, thick with manzanita, huckleberry, and burnt timber.	+300
80.00	Set post for corner of secs. 8, 9, 16 and 17; from which	
	A fir, 8 in. in dia., bears S.2 $\frac{1}{2}$ °W., 40 lks. dist.	