

Subdivisions of T. 20 S., R. 10 W.

CHAINS

A fir, 8 in. in dia., bears S.69½°E., 58 lks. dist.
 Threw up mound, etc., as per instructions.

TO HERE

North between secs. 8 and 9.

Var. 20° East.

Commence ascent.

- 1.00 Top of mountain, course E. & W.; commence descending. +50
- 7.20 Gulch, course SW. -150
- 7.50 Enter timber flat. +30
- 22.00 Commence descent.
- 25.00 Gulch, course SW. -80
- 32.00 Top of spur, course E. & W. +200
- 38.00 Branch, course SW., 20 lks. wide. -250
- Commence ascending a steep rocky spur, with burnt timber.
- 40.00 Set ¼ sec. post by marking a boulder, 3 ft. by 2 by 6 ft. +100
 No timber accessible and the rocky nature of the ground
 not allowing any pits.
- Keep ascending.
- 54.00 Top of ridge, all burnt clear; thence along South slope
 of ridge, near summit, gradually ascending. +200
- 70.00 Enter green timber.
- 80.00 Set post to corner of secs. 8, 9, 5 and 4, on top of flat +80
 ridge; from which

An alder, 10 in. in dia., bears N.72°E., 35 lks. dist.

An alder, 8 in. in dia., bears N.69°W., 53 lks. dist.

A fir, 42 in. in dia., bears S.60°W., 55 lks. dist.

A fir, 36 in. in dia., bears S.30°E., 85 lks. dist.

Feb. 28, 1878.

From post to cor. of secs. 7, 8, 17 and 18,

North between secs. 7 and 8.

Var. 20° East.

Commence ascending.

- .50 Top of rise. +20
- 1.25 Gulch, course NE.; commence steep ascent. -60
- 7.25 Top of spur, course E. & W. +250