

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 20 S., R. 10 W.

CHAINS		
8.00	Chapman's house bears N.80°E.	
14.00	Top of spur, course E. & W.	+120
16.75	Canyon, course E., rocky bluff.	-100
19.00	Top of spur; commence descending East slope.	+75.
24.50	Top of spur, course East.	-30
36.30	Sulphur Creek, course SE., 15 lks. wide.	-60
40.00	Set $\frac{1}{2}$ sec. post; from which	+120
	A maple, 5 in. in dia., bears S.32°W., 18 lks. dist.	
	A maple, 7 in. in dia., bears S.70 $\frac{1}{2}$ °E., 49 lks. dist.	
	Keep ascending West slope of burnt hill.	
63.00	Top of divide between waters of Sulphur and Harlan Creeks, course N.30°W. and S.30°E.	+700
	Commence descending East slope.	
79.75	Gulch, course East.	-400
80.00	Set post for corner to secs. 5, 6, 7 and 8; from which	+10
	A fir, 48 in. in dia., bears S.65°W., 76 lks. dist.	
	A maple, 4 in. in dia., bears N.69 $\frac{1}{2}$ °E., 33 lks. dist.	
	A fir, 48 in. in dia., bears N.42°W., 111 lks. dist.	
	A fir, 16 in. in dia., bears S.68°E., 103 lks. dist.	
	March 1st, 1878.	
	East, on random line, bet. secs. 5 and 8.	
79.30	Intersect south 30 lks. of post to cor. of secs. 8, 9, 4 and 5.	
	Thence S.89°47'W., on true line, between secs. 5 and 8.	
	Var. 20° East.	
	Commence descent steep open mountain, with few trees.	
9.00	Bench.	-250
10.00	Leave bench; descend towards river.	
14.65	Set flag on top of bluff, 200 ft. above river; cross over into line. Lay off base S.13'E.; back flag on top of bluff bears N.77°E., making 4.35 departure.	-80
19.00	To west bank of river, course S., 90 lks. wide.	-190
28.00	Harlan's house bears South about 12 chs.	
30.00	Keep ascending; leave clearing.	
39.65	Set $\frac{1}{2}$ sec. post; from which	+60