

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 10 W.

CHAINS

22.00 Top of ridge; thence along the east slope of Burnt Mountain. +460

40.00 For post a maple tree, 12 in. diam.; from which  
A maple tree, 6 in. dia., bears N.78°E., 33 lks.  
No other tree convenient to the line.

West Bdy. of T. 20 S., R. 9 W.  
Survey by Wm. Thiel under Contract 567 dated Feb. 16, 1891.

At the cor. of secs. 30 and 31, on the west boundary, the post being gone, I re-establish the corner to secs. 25, 30, 31 and 36, Tps. 20 S., Rs. 9 and 10 W. by setting a sandstone, 12x12x4 ins., 8 ins. in the ground, marked 1 notch on S. and 5 notches on N. edges; from which  
An alder, 20 ins. dia., bears N.52°E., 75 lks. dist., marked T 20 S R. 9 W S 30 B T.  
A cedar, 72 ins. dia., bears S.60°E., 30 lks. dist., marked T 20 S R 9 W S 31 B T.  
An alder, 24 ins. dia., bears S.85°W., 13 lks. dist., marked T. 20 S R 10 W S 36 B T.  
A hemlock, 20 ins. dia., bears N.50°W., 28 lks. dist., marked T 20 S R 10 W S 25 B T.

Thence I run  
North, bet. secs. 30 and 25.

Va. 20°6'E.

1.00 A gulch, course W.  
7.00 A canyon, course W.; begin ascent of W. slope.  
24.75 A canyon, course S.10°W.; steep ascent.  
36.50 Top of ridge, bears SW. and NE.  
39.70 Top of ridge, bears NW. and SE.  
40.00 An alder, 6 ins. dia., which I mark  $\frac{1}{2}$  S on W. side, for  $\frac{1}{4}$  sec. cor.; from which  
An alder, 7 ins. dia., bears S.54°W., 5 lks. dist., marked  $\frac{1}{2}$  S B T.  
A chitten, 4 ins. dia., bears S.18°E., 18 lks. dist., marked  $\frac{1}{2}$  S B T.