

West Bdy. of T. 20 S., R. 9 W.

CHAINS	Continue steep descent of NE. slope.	
52.75	A canyon, course E.	
54.80	Top of spur, bears E. & W.	+45
58.20	A canyon, course E.	-50
60.00	A gulch, course SE.	
68.75	Top of spur, bears E. & W.	
	Leave green fir timber; enter burnt timber.	+120
70.00	Leave the burnt; enter green timber.	
78.00	A canyon, course E.	-150
80.00	Set a sandstone, 20x18x12 ins., 15 ins. in the ground, for corner to secs. 19, 24, 25, and 30, marked with 2 notches on S. and 4 notches on N. edges; from which A maple, 18 ins. dia., bears N.87°E., 94 lks. dist., marked T 20 S R 9 W S 19 B T. A fir, 50 ins. dia., bears N.3½°W., 53 lks. dist., marked T 20 S R 10 W S 24 B T. A maple, 15 ins. dia., bears S.30°W., 75 lks. dist., marked T 20 S R 10 W S 25 B T. A cedar, 27 ins. dia., bears S.3°E., 225 lks. dist., marked T 20 S R 9 W S 30 B T.	

Sept. 9th, 1891.

---

North bet. secs. 24 and 19.

Var. 20° 8' E.

Ascend.

5.50	A canyon, course SE.	-100
8.20	Top of spur, bears E. & W.	+130
12.25	A canyon, course E.	-80
26.50	Top of spur, bears E. & W.	+120
33.25	A canyon, course NE.	-100
39.00	Top of spur, bears NE. and SW.	+80
40.00	Set a post, 3 ft. long, 3 ins. square, 18 ins. in the ground, for ¼ sec. cor., marked ¼ S on W. face; from which An alder, 3 ins. in dia., bears S.5°E., 27 lks. dist.,	