

County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 20 S., R. 9 W.

CHAINS		
	marked $\frac{1}{4}$ S B T.	
	An elder, 3 ins. in dia., bears N.45°W., 95 lks. dist.,	
	marked $\frac{1}{4}$ S B T.	
47.00	A canyon, course E.	
59.50	Top of ridge, bears SE. and NW.	
71.00	A branch, 5 lks. wide, course S.60°E.; begin ascent.	
77.50	Top of ascent; begin descent of E. slope.	
80.00	A fir, 10 ins. dia., which I mark T 20 S S 18 on NE., R 9 W S 19 on SE., R 10 W S 24 on SW., S 13 on NW. sides, with 3 notches on N. and S. sides, for corner to secs. 18, 19, 13 and 24; from which	
	A fir, 48 ins. dia., bears N.30°E., 30 lks. dist., marked T 20 S R 9 W S 18 B T.	
	A fir, 48 ins. dia., bears S.7 $\frac{1}{2}$ °E., 18 lks. dist., marked T 20 S R 9 W S 19 B T.	
	A fir, 30 ins. dia., bears S.60°W., 110 lks. dist., marked T 20 S R 10 W S 24 B T.	
	A fir, 24 ins. dia., bears N.75°W., 38 lks. dist., marked T 20 S R 10 W S 13 B T.	
North bet. secs. 13 and 18.		
Var. 20° 2' E.		
	Ascend W. slope.	
5.40	A canyon; course S.5°W.; steep ascent.	+50
12.30	A canyon, course SW.	+120
18.75	Top of ridge, bears E. & W.; begin descent of E. slope.	+350
24.00	A sag; begin ascent.	-50
30.00	Top of dividing ridge; begin descent of W. slope.	+100
33.75	A canyon, course W.	
36.20	Top of spur, bears E. & W.	
37.50	A canyon, course W.	
40.00	Set a post, 4 ft. long, 4 ins. square, 18 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which	
	A fir, 36 ins. dia., bears S.8°E., 67 lks. dist.,	