

County Surveyor's Record, Douglas County, Oregon

North Bdy. of T. 20 S., R. 9 W.

CHAINS

and S 34 on NW. faces, with 2 notches on E. and 4 notches on W. edges; from which

A cedar, 18 ins. dia., bears N.80°E., 37 lks. dist., marked T 19 S R 9 W S 35 B T.

A hemlock, 20 ins. in dia., bears S.19½°E., 11 lks. dist., marked T 20 S R 9 W S 2 B T.

A fir, 24 ins. in dia., bears S.81°W., 52 lks. dist., marked T 20 S R 9 W S 3 B T.

A fir, 36 ins. in dia., bears N.76°W., 64 lks. dist., marked T 19 S R 9 W S 34 B T.

Thence I run

East, on true line, bet. secs. 35 and 2.

Var.20°8'E.

Ascend.

- 5.65 Top of spur, bears NE. & SW.; begin steep descent. +100
- 17.25 A canyon, course SE.; keep on descending. -380
- 24.40 A gulch, course S.; begin ascent of a moderate S. slope. -50
- 38.00 Top of spur, bears E. & W.; begin descent.
- 40.00 Set a chittem post, 3 ft. long, 3 ins. square, 18 ins. in the ground, for ¼ sec. cor., marked ¼ S on N. face; from which
 - An alder, 10 ins. dia., bears S.10°E., 7 lks. dist., marked ¼ S B T.
 - An alder, 12 ins. dia., bears N.27°E., 12 lks. dist., marked ¼ S B T.
- 44.60 Beaver Creek, 15 lks. wide, course S.5°E.; begin ascent.
- 46.75 Top of spur, bears SW. and NE.; begin descent.
- 48.00 A gulch, course SW.; begin steep ascent.
- 50.50 Ascent moderate.
- 79.00 Top of ridge, bears NW. and SE.; begin descent.
- 80.00 A cedar, 8 ins. in dia., which I marked for cor. to secs. 1, 2, 35 & 36: T 19 S S 36 on NE., R 9 W S 1 on SE., T 20 S S 2 on SW., S 35 on NW. sides, with 1 notch on E. and 5 notches on W. sides; from which
 - A fir, 24 ins. dia., bears N.57°E., 14 lks. dist.,