

County Surveyor's Record, Douglas County, Oregon

North Bdy. of T. 20 S., R. 9 W.

CHAINS 72.50	Top of rise; begin descent.	+60
82.75	A gulch, course S.	-200
90.50	A gulch, course S.; descend along S. slope.	
99.00	Set temporary corner until this NE. corner of Section 1, T. 20 S., R. 9 W. has been established by running a line North from the NW. cor. of Sec. 6, T.20 S.,R. 8 W.	
<p>From corner to Tps. 19 and 20 S., R. 8 W., which is a post, 6 ins. square, 24 ins. above ground, firmly set, marked T 19 S S 31 on NE., R 8 W S 6 on SE., T 20 S S 1 on SW., R 9 W S 36 on NW. faces, with 6 notches on each edge; from which</p> <p>A fir, 30 ins. diam., bears N.48°E., 23 lks. dist., marked T 19 S R 8 W S 31 B T.</p> <p>A fir, 20 ins. diam., bears S.7°E., 43 lks. dist., marked T 20 S R 8 W S 6 B T.</p> <p>A hemlock, 8 ins. diam., bears S.81°W., 37 lks. dist., marked T 20 S R 9 W S 1 B T.</p> <p>A fir, 30 ins. diam., bears N.53°W., 78 lks. dist., marked T 19 S R 9 W S 36 B T.</p> <p>I run North bet. secs. 1 and 31.</p> <p style="text-align: right;">Var. 20°4'E.</p> <p>Descend W. slope.</p>		
4.50	Foot of mountain.	-80
5.00	West branch, 120 lks. wide, course S.60°W.	
	October 7th, 1891.	
7.70	A fir, 36 ins. diam., which I marked with 2 notches on N. and S. sides.	
9.50	Begin ascent.	
22.50	Top of rise; begin descent.	+90
27.40	A gulch, course S.30°E.; still ascending E. slope.	
37.80	Intersect E. and W. line bet. secs. 1 and 36, 25 lks. West of temporary post.	
	Set a vine maple post, 4½ ft. long, 4 ins. square, 24 ins. in the ground, for closing corner to Tps. 19 and	