

North Bdy. of T. 20 S., R. 9 W.

CHAINS

20 S., R. 9 W., marked C C T 19 S S 36 on N., R 8 W on E., T 20 S S 1 on S., C C R 9 W on W. faces, with 6 notches on N., S. & W. faces; from which

A fir, 16 ins. in dia., bears S.55 $\frac{1}{2}$ °E., 30 lks.dist., marked C C T 19 & 20 S R 9 W B T.

A fir, 42 ins. in dia., bears S.70°W., 11 lks. dist., marked T 20 S R 9 W S 1 B T.

A fir, 40 ins. in dia., bears N.35 $\frac{1}{2}$ °W., 30 lks.dist., marked T 19 S R 9 W S 36 B T.

October 8th, 1891.

Exteriors of T. 20 S., R. 10 W. as surveyed by Nathaniel Martin under Contract 599 dated June 20th, 1892.

I now go to the cor. of Tps. 20 and 21 S., Rs. 9 and 10 W., which is a cedar post, 5 ins. sq., 2 $\frac{1}{2}$ ft. above ground and marked T 20 S Sec 31 on NE., R 9 W Sec 6 on SE., T 21 S Sec 1 on SW., R 10 W Sec 36 on NW. faces, with 6 notches on each edge; from which

A maple, 14 ins. diam., bears N.64°E., dist. 74 lks., marked T 20 S R 9 W Sec 31 B T.

Maple, 12 ins. diam., bears S.12 $\frac{1}{2}$ °E., dist. 49 lks., marked T 20 S R 9 W Sec 6 B T.

A fir, 36 ins. diam., bears S.33 $\frac{1}{4}$ °W., dist. 44 lks., marked T 21 S R 10 W Sec 1 B T.

Fir, 24 ins. diam., bears N.32 $\frac{1}{2}$ °W., dist. 65 lks., marked T 20 S R 10 W Sec 36 B T.

Thence I run

West, on random line, between secs. 1, 2, 35 and 36.

Va.19°E.

Setting temporary corner posts at each 40 and 80 chains.

160.00 I find that the cor. post of secs. 34, 35, 2 and 3, with all the bearing trees have been entirely destroyed by fire; therefore, to reestablish this corner I set a temporary post, then I go to the $\frac{1}{4}$ sec. cor. north on line bet. secs. 34 and 35, which is a post, 3 $\frac{1}{2}$ ins.