

County Surveyor's Record, Douglas County, Oregon

South Bdy. of T. 20 S., R. 10 W.

CHAINS

sq., $2\frac{1}{2}$ ft. above ground and marked $\frac{1}{4}$ S on west face;
from which

An alder, 3 ins. diam., bears N.70°W., dist. 3 lks.,
marked $\frac{1}{4}$ S B T.

Alder, 5 ins. diam., bears N.45°E., dist. 7 lks.,
marked $\frac{1}{4}$ S B T.

Thence I run

South 2'E., between secs. 34 and 35.

Va.19°E.

40.00 Set temp. post.

Thence I run West from this temporary cor. on random line
bet. secs. 3 and 34.

Va.19°E.

40.21 Intersect 20 lks. North of the $\frac{1}{4}$ sec. cor. on south bdy.
of Sec. 34, which is a post, marked $\frac{1}{4}$ S on N. face;
from which

An alder, 6 ins. diam., bears N.42°E., dist. 20 lks.,
marked $\frac{1}{4}$ S B T,

Alder, 5 ins. diam., bears S.35°E., dist. 15 lks.,
marked $\frac{1}{4}$ S B T.

Thence I run

North 89°42'E., on true line, on south bdy. of Sec. 34.

Va.19°E.

40.10 Intersect $10\frac{1}{2}$ lks. West of temp. cor. last named, here
I set post, 4 ft. long, 4 ins. sq., 24 ins. in the
ground, for cor. of secs. 34, 35, 2 and 3, and marked
T 20 S Sec 35 on NE., R 10 W Sec 2 on SE., T 21 S Sec
3 on SW., Sec 34 on NW. faces, with 4 notches on W. and
2 on E. edges; from which

A fir, 60 ins. diam., bears S.37 $\frac{1}{2}$ °E., dist. 381 lks.,
marked T 21 S R 10 W Sec 2 B T.

Cedar, dead, 36 ins. diam., bears N.36°E., dist.
175 lks., marked T 20 S R 10 W Sec 3 B T.

No other trees in limits and no stone near to be
found; I then