

East Bdy. of T. 20 S., R. 10 W.

CHAINS
60.00

Canyon, course SW.

73.00

Top of ridge, course NE.

88.80

On N. slope of hill, set post, 4 ft. long, 4 ins. sq.,
24 ins. in the ground, for cor. of Tps. 19 and 20 S.,
Rs. 9 and 10 W., marked T 19 S R 9 W Sec 31 on NE., R
9 W Sec 6 on SE., T 20 S R 10 W Sec 1 on SW., R 10 W
Sec 36 on NW. faces, with 6 notches on S., E. and W.
faces; from which a

Fir, 12 ins. diam., bears N.20°E., dist. 56 lks.,
marked T 19 S R 9 W Sec 31 B T.

Fir, 10 ins. diam., bears N.34°W., dist. 76 lks.,
marked T 19 S R 10 W Sec 36 B T.

Hemlock, 8 ins. diam., bears S.63°W., dist. 80 lks.,
marked T 20 S R 10 W Sec 1 B T.

Hemlock 14 ins. diam., bears S.21°E., dist. 91 lks.,
marked T 20 S R 9 W Sec 6 B T.

Sept. 1st, 1892.

From the cor. of Tps. 19 and 20 S., Rs. 9 and 10 W., I
run

West, on random line, bet. Tps. 19 and 20 South.

Va. 19 $\frac{1}{2}$ °E.

setting temp. half mile and mile cors. at each 40.00
and 80.00 chs., and find the line to be 6 miles, 1.75
chs. long, and the falling to be 1.50 chs. N. of the
cor. of Tps. 20 S., Rs. 10 and 11 W., which is a sand-
stone, 4 ins. above ground, and marked C C with 6
notches on N., E. and W. faces, with mound of stone,
1 $\frac{1}{2}$ ft. high and 2 ft. base, alongside.

Thence I run

N.89°49'E., on true line, bet. secs. 6 and 31.

Va. 19 $\frac{1}{2}$ °E.

41.75 Over burned hills to high ridge.

Set a sandstone, 6x8x10 ins., 6 ins. in ground, for $\frac{1}{4}$
sec. cor., marked $\frac{1}{4}$ S on N. face; and raised a mound