

County Surveyor's Record, Douglas County, Oregon

North Bay. of T. 20 S., R. 10 W.

CHAINS

for cor. to secs. 4, 5, 32 and 33, marked T 19 S Sec 33 on NE., T 20 S Sec 4 on SE., R 10 W Sec 5 on SW., Sec 32 on NW. faces, with 4 notches on E. and 2 on W. edges; from which an

Alder, 6 ins. diam., bears N.5°E., dist. 7 lks., marked T 19 S R 10 W Sec 33 B T.

Maple, 4 ins. diam., bears S.75°E., dist. 15 lks., marked T 20 S R 10 W Sec 4 B T.

Fir, 7 ins. diam., bears S.85°W., dist. 15 lks., marked T 20 S R 10 W Sec 5 B T.

Fir, 8 ins. diam., bears N.65°W., dist. 45 lks., marked T 19 S R 10 W Sec 32 B T.

Sept. 6th, 1892.

N.89°49'E., on true line, bet. secs. 4 and 33.

Va. 19½°E.

Ascend.

25.00 Top of high ridge, course SE.; descend. +200

40.00 Canyon, course NW. -200

Set post, 4 ft. long, 3½ ins. sq., 24 ins. in ground, for ¼ sec. corner, marked ¼ S on N. face; from which a

Maple, 5 ins. diam., bears N.15°E., dist. 15 lks., marked ¼ S B T.

Chitten, 4 ins. diam., bears S.20°W., dist. 150 lks., marked ¼ S B T.

Ascend.

59.00 Top of hill; descend.

70.00 Dry gulch; ascend.

80.00 Hillside, set post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. of secs. 3, 4, 33 and 34, marked T 19 S R 10 W Sec 34 on NE., T 20 S R 10 W Sec 3 on SE., Sec 4 on SW., Sec 33 on NW. faces, with 3 notches on E. and W. edges. No green timber within limits; raised mound of stone around post, 18 ins. high and 30 ins. base. Pits impracticable.

Sept. 6, 1892.