

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 10 W.

CHAINS

Fir, 6 ins. diam., bears S.41°W., dist. 200 lks.,
marked $\frac{1}{4}$ S B T.

41.00 Branch, 5 lks. wide, course NE.

57.00 Branch, 4 lks. wide, course NE.

80.30 Cor. of secs. 1, 2, 35, and 36.

Sept. 10, 1892.

From cor. of secs. 25, 26, 35, and 36, I run
North 1' W., bet. secs. 25 and 26.

Va.19°E.

Ascend.

30.00 Cross dry-gulch to top of ridge.

40.00 In head of canyon, course SW.

Set post, 48 ins. long, 4 ins. sq., 24 ins. in the ground,
for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ S on W. face; from which a
Fir, 40 ins. diam., bears S.10°E., dist. 6 lks.,
marked $\frac{1}{4}$ S B T.

Fir, 20 ins. diam., bears N.34°E., dist. 70 lks.,
marked $\frac{1}{4}$ S B T.

45.00 Top of ridge, course NE.; descend.

70.00 Creek, 12 lks. wide, course W.; ascend hill on N. slope.

80.00 Set post, 48 ins. long, 4 ins. sq., 24 ins. in the ground,
for cor. of secs. 23, 24, 25, and 26, marked T 20 S
Sec 24 on NE., R 10 W Sec 25 on SE., Sec 26 on SW.,
Sec 23 on NW. faces, 2 notches on S. and 1 on E. edges;
from which a

Fir, 30 ins. diam., bears N.50°E., dist. 40 lks.,
marked T 20 S R 10 W Sec 24 B T.

Alder, 12 ins. diam., bears S.37°E., dist. 10 lks.,
marked T 20 S R 10 W Sec 25 B T.

Alder, 10 ins. diam., bears S.61°W., dist. 50 lks.,
marked T 20 S R 10 W Sec 26 B T.

Alder, 8 ins. diam., bears N.61 $\frac{1}{2}$ °W., dist. 45 lks.,
marked T 20 S R 10 W Sec 23 B T.

Sept. 11th, 1892.