

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 10 W.

CHAINS
80.40

Intersect W. bdy. of Sec., 45 lks. S. of cor. to secs. 22, 23, 26, and 27, which is a post, 30 ins. above ground, marked T. 20 S. Sec 23 on NE., R 10 W Sec 26 on SE., Sec 27 on SW., Sec 22 on NW. faces, 2 notches on S. and E. edges; from which a

Maple, 4 ins. diam., bears N. $31\frac{1}{2}^{\circ}$ E., dist. 6 lks., marked T 20 S R 10 W Sec 23 B T.

Fir, 12 ins. diam., bears S. $42\frac{1}{2}^{\circ}$ E., dist. 46 lks., marked T 20 S R 10 W Sec 26 B T.

Fir, 42 ins. diam., bears S. $75\frac{1}{2}^{\circ}$ W., dist. 38 lks., marked T 20 S R 10 W Sec 27 B T.

Fir, 48 ins. diam., bears N. 60° W., dist. 38 lks., marked T 20 S R 10 W Sec 22 B T.

Thence I run

S. $89^{\circ}41'$ E., on true line, bet. secs. 23 and 26.

Va. 19° E.

3.00 Cross bottom land to Spencer Creek, 60 lks. wide, course South.

25.00 Cross bottom land to foot of hill; ascend N. slope of hill and

40.20 Marked a chittem tree, 6 ins. diam., for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which a

Fir, 10 ins. diam., bears N. 55° W., dist. 4 lks., marked $\frac{1}{4}$ S B T.

Fir, 6 ins. diam., bears S. 60° E., dist. 170 lks., marked $\frac{1}{4}$ S B T.

70.00 Along N. slope of hill; ascend hillside.

80.40 Corner of secs. 23, 24, 25, and 26.

Sept. 13, 1892.

From the cor. of secs. 23, 24, 25, and 26, I run

North $1'$ W., bet. secs. 23 and 24.

Va. 19° E.

3.00 Top of hill, course E.; descend.

19.50 Dry gulch, course W.; ascend hill.