

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 10 W.

CHAINS

Fir, 30 ins. diam., bears S.60°W., dist. 110 lks.,
marked T 20 S R 10 W Sec 24 B T.

Fir, 24 ins. diam., bears N.75°W., dist. 38 lks.,
marked T 20 S R 10 W Sec 13 B T.

Thence I run

West, on true line, bet. secs. 13 and 24.

Va.19°E.

Ascend.

15.00 Top of ridge; descend.

25.00 Foot of hill; ascend.

39.95 Top of ridge, course N.

Set post, 4 ft. long, 3½ ins. sq., 24 ins. in ground, for

¼ sec. cor., marked ¼ S on N. face; from which a

Fir, 18 ins. diam., bears N.10°E., dist. 60 lks.,

marked ¼ S B T.

Fir, 10 ins. diam., bears S.20°W., dist. 80 lks.,

marked ¼ S B T.

Descend.

75.00 Dry gulch; ascend.

79.90 To cor. of secs. 13, 14, 23, and 24.

Sept. 15, 1892.

From cor. of secs. 13, 14, 23 and 24, I run

North 1' West, on line bet. secs. 13 and 14.

Va.19°E.

9.00 Top of high ridge, course NW.; descend.

+200

18.00 Fir tree, 30 ins. diam., on line, marked 2 notches on N.
and S. sides.

35.00 Ravine, course SE.; ascend.

40.00 Dry gulch, course SW.; ascend.

Set post, 4 ft. long, 3½ ins. sq., 24 ins. in ground, for

¼ sec. cor., marked ¼ S on W. face; from which a

Hemlock, 10 ins. diam., bears N.47°W., dist. 70 lks.,

marked ¼ S B T.