

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 10 W.

CHAINS

marked $\frac{1}{4}$ S B T.

Hemlock, 20 ins. diam., bears S.80°W., dist. 200 lks., marked $\frac{1}{4}$ S B T.

60.00 Branch, 3 lks. wide, course SW.; ascend.

80.29 Cor. of secs. 11, 12, 13 and 14.

Sept. 17, 1892.

From cor. of secs. 11, 12, 13 and 14, I run North 1°W., bet. secs. 11 and 12.

Va.19°E.

Ascend.

20.00 Descend to foot of hill.

30.00 Canyon, course SW.; ascend.

40.00 Top of spur of ridge; descend.

Set post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which a Cedar, 6 ins. diam., bears S.36°E., dist. 69 lks., marked $\frac{1}{4}$ S B T.
Maple, 7 ins. diam., bears N.40°W., dist. 60 lks., marked $\frac{1}{4}$ S B T.

59.00 Ascend ridge, course NE.

74.00 On same ridge.

80.00 On W. slope of ridge.

Set post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. of secs. 1, 2, 11, and 12, marked T 20 S Sec 1 on NE., R 10 W Sec 12 on SE., Sec 11 on SW., Sec 2 on NW. faces, 5 notches on S. and 1 on E. edges; from which a

Fir, 20 ins. diam., bears N.60°E., dist. 73 lks., marked T 20 S R 10 W Sec 1 B T.

Fir, 10 ins. diam., bears S.70°E., dist. 100 lks., marked T 20 S R 10 W Sec 12 B T.

Fir, 15 ins. diam., bears S.19°W., dist. 150 lks., marked T 20 S R 10 W Sec 11 B T.

Hemlock, 8 ins. diam., bears N.27°W., dist. 76 lks.,