

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 10 W.

CHAINS

for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which a
 Fir, 30 ins. diam., bears N.59°W., dist. 73 lks.,
 marked $\frac{1}{4}$ S B T.

Fir, 30 ins. diam., bears S.63°E., dist. 73 lks.,
 marked $\frac{1}{4}$ S B T.

50.00 Top of hill, course NW.

65.00 Dry gulch, course SE.

88.70 Cor. of secs. 1, 2, 11, and 12.

Sept. 20, 1892.

From cor. to secs. 22, 23, 26, and 27, I run
 North 2' W., bet. secs. 22 and 23.

Va.19°E.

10.00 Foot of hill; ascend.

25.00 Top of ridge, course NW.; descend.

36.00 Ravine, course SE.

40.00 On S. slope of hill.

Set post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for
 $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which a
 Fir, 8 ins. diam., bears N.15°E., dist. 63 lks.,
 marked $\frac{1}{4}$ S B T.

Hemlock, 10 ins. diam., bears S.30°E., dist. 72 lks.,
 marked $\frac{1}{4}$ S B T.

Ascend.

67.00 Top of ridge, course NE.; descend.

80.00 In gulch, set post, 4 ft. long, 4 ins. sq., 24 ins. in
 the ground, for cor. of secs. 14, 15, 22, and 23, marked
 T 20 S Sec 14 on NE., R 10 W Sec 23 on SE., Sec 22 on
 SW., Sec 15 on NE. face, with 3 notches on S. and 2
 notches on E. edges; from which a

Hemlock, 12 ins. diam., bears N.23°E., dist. 76 lks.,
 marked T 20 S R 10 W Sec 14 B T.

Chittem, 7 ins. diam., bears S.40°E., dist. 81 lks.,
 marked T 20 S R 10 W Sec 23 B T.

Fir, 10 ins. diam., bears S.12°W., dist. 86 lks.,