

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 10 W.

CHAINS

Maple, 10 ins. diam., bears S.60°W., dist. 43 lks.,  
marked  $\frac{1}{4}$  S B T.

49.00 A hemlock, 24 ins. diam., on line, with 2 notches on N.  
and S. sides.

60.00 Dry gulch, course E.

80.00 On N. slope of hill.

Set post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for  
cor. of secs. 10, 11, 14, and 15, marked T 20 S Sec 11  
on NE., R 10 W Sec 14 on SE., Sec 15 on SW., Sec 10 on  
NW. faces, 4 notches on S. and 2 on E. edges; from  
which a

Hemlock, 20 ins. diam., bears N.70°E., dist. 76 lks.,  
marked T 20 S R 10 W Sec 11 B T.

Fir, 10 ins. diam., bears S.41°E., dist. 64 lks.,  
marked T 20 S R 10 W Sec 14 B T.

Alder, 5 ins. diam., bears S.23°W., dist. 14 lks.,  
marked T 20 S R 10 W Sec 15 B T.

Alder, 7 ins. diam., bears N.54°W., dist. 30 lks.,  
marked T 20 S R 10 W Sec 10 B T.

Sept. 22, 1892.

From cor. of secs. 10, 11, 14, and 15, I run  
S.89°52'E., on random line, bet. secs. 11 and 14.

Va.19°E.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.50 Intersect E. hdy. of Sec., 23 lks. S. of cor. of secs.  
11, 12, 13, and 14.

Thence I run

S.89°58'W., on true line, bet. secs. 11 and 14.

Va.19°E.

40.25 Over rolling ridges.

Set post, 4 ft. long, 4 ins. sq., 24 ins. in ground, for  
 $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S on N. face; from which a

Maple, 9 ins. diam., bears N.44°W., dist. 40 lks.,  
marked  $\frac{1}{4}$  S B T.