

Subdivisions of T. 20 S., R. 10 W.

CHAINS

Alder, 6 ins. diam., bears S.50°W., dist. 60 lks.,
marked $\frac{1}{4}$ S B T.

60.00 Canyon, course SW. -100

80.50 Along N. slope of ridge to the cor. of secs. 10, 11, 14,
and 15.

Sept. 22, 1892.

From cor. of secs. 10, 11, 14, and 15, I run
North 2' West, bet. secs. 10 and 11.

Va.19°E.

Descend.

4.00 Dry gulch, course E.; ascend.

24.00 Top of ridge, course NW.; descend.

40.00 Canyon, course SW.; ascend.

Set post, 4 ft. long, $3\frac{1}{2}$ ins. sq., 24 ins. in the ground,
for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which an
Alder, 8 ins. diam., bears N.36°W., dist. 60 lks.,
marked $\frac{1}{4}$ S B T.

Alder, 6 ins. diam., bears S.41°E., dist. 71 lks.,
marked $\frac{1}{4}$ S B T.

Ascend.

57.00 Top of ridge, course NW.; descend. +200

65.00 Canyon, course SE.; ascend. -200

80.00 Near top of ridge, course NW.

Set post, $4\frac{1}{2}$ ft. long, 4 ins. sq., 24 ins. in ground, for
cor. of secs. 2, 3, 10, and 11, marked T 20 S Sec 2 on
NE., R 10 W Sec 11 on SE., Sec 10 on SW., Sec 3 on NW.
faces, 5 notches on S. and 2 on E. edges; from which a
Fir, 30 ins. diam., bears N.73°E., dist. 70 lks.,
marked T 20 S R 10 W Sec 2 B T.

Fir, 25 ins. diam., bears S.61°E., dist. 80 lks.,
marked T 20 S R 10 W Sec 11 B T.

Fir, 20 ins. diam., bears S.27°W., dist. 75 lks.,
marked T 20 S R 10 W Sec 10 B T.

Fir, 22 ins. diam., bears N.44°W., dist. 87 lks.,
marked T 20 S R 10 W Sec 3 B T.

Sept. 22, 1892.