

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 10 W.

CHAINS

From cor. to secs. 2, 3, 10, and 11, I run
 N.89°58'E., on random line, bet. secs. 2 and 11.
 Va.19°E.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.31 Intersect E. bdy. of sec. at the cor. of secs. 1, 2, 11,
 and 12.
 Thence I run
 S.89°58'W., on true line, bet. secs. 2 and 11.
 Va.19°E.

19.00 Hemlock tree, 20 ins. diam., on line, 2 notches on E. and
 W. sides.

40.15 $\frac{1}{2}$ Set post, 4 ft. long, 3 $\frac{1}{2}$ ins. sq., 24 ins. in ground, for
 $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which a
 Fir, 12 ins. diam., bears N.53°W., dist. 84 lks.,
 marked $\frac{1}{4}$ S B T.
 Fir, 10 ins. diam., bears S.45°E., dist. 78 lks.,
 marked $\frac{1}{4}$ S B T.

55.00 Canyon, course S.; ascend.

65.00 Top of ridge, course NW.; descend.

72.00 Fir, 30 ins. diam., on line, marked 2 notches on E. and
 W. sides.

80.31 Cor. of secs. 2, 3, 10, and 11.
 Sept. 23, 1892.

From cor. of secs. 2, 3, 10, and 11, I run
 N. 13' E., on random line, bet. secs. 2 and 3.
 Va.19°E.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

88.90 Intersect N. bdy. of Tp., 4 lks. E. of cor. of secs. 2,
 3, 34, and 35.
 Thence I run
 South 9' W., on true line, bet. secs. 2 and 3.
 Va.19°E.

10.00 Fir, 30 ins. diam., on line, marked 2 notches on N. and
 S. sides.